

WHAT IS CLAIMED IS:

- Sub 1
- 5 1. A device for compressing the chest of a patient comprising:
 a band adapted to extend around the chest of the patient;
 a driver mechanism, operably connected to the band, for
 circumferentially contracting the band;
 a fluid-filled cushion disposed between the chest of the
 patient and the band; and
 an automatic controller for controlling operation of the
 driver mechanism.
- 10 2. A device for compressing the chest of a patient comprising:
 a band adapted to extend around the chest of the patient, the
 band having a length and a plurality of fluid-receiving
 cells disposed along the length of the band;
 a driver mechanism, operably connected to the band, for
 inflating the fluid-receiving cells;
 a cushion disposed between the chest of the patient and the
 band; and
 an automatic controller for controlling operation of the
 driver mechanism.
- 15 3. The device of claim 2, wherein the cushion is a sealed
 cushion.
- 20 4. The device of claim 2, wherein the band is comprised of an
 inelastic material.
- 25 5. A device for compressing the chest of a patient comprising:
 a band adapted to extend around the chest of the patient, the
 band having a length and a plurality of fluid-receiving
 cells disposed along the length of the band, wherein the
- Sub B2

plurality of fluid-receiving cells are in fluid communication with each other;

a driver mechanism, connected to the band and the fluid-receiving cells, for inflating the fluid-receiving cells;

5 a cushion disposed between the chest of the patient and the band; and

an automatic controller for controlling the operation of the driver mechanism.

6. The device of claim 5, wherein the cushion is a sealed cushion.

7. The device of claim 5, wherein the band is comprised of an inelastic material.

8. A device for compressing the chest of a patient comprising:

a band adapted to extend around the chest of the patient, the band having a length and a plurality of fluid-receiving cells disposed along the length of the band, each fluid-receiving cells being interconnected to another fluid-receiving cells by a linking portion;

a driver mechanism, operably connected to the band, for inflating the fluid-receiving cells;

a cushion disposed between the chest of the patient and the band; and

an automatic controller for controlling operation of the driver mechanism.

9. The device of claim 8, wherein the cushion is a sealed cushion.

10. The device of claim 8, wherein the band is comprised of an inelastic material.

11. A device for compressing the chest of a patient comprising:

a band adapted to extend around the chest of the patient, the band having a length and a plurality of fluid-receiving cells disposed along the length of the band, each fluid-receiving cells being interconnected to another fluid-receiving cell by a linking portion, wherein the plurality of fluid-receiving cells are in fluid communication with each other;

a driver mechanism, connected to the band and the fluid-receiving cells, for inflating the fluid-receiving cells;

a cushion disposed between the chest of the patient and the band; and

an automatic controller for controlling the operation of the driver mechanism.

12. The device of claim 11, wherein the cushion is a sealed cushion.

13. The device of claim 11, wherein the band is comprised of an inelastic material.